

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 07-251043

(43)Date of publication of application : 03.10.1995

(51)Int.Cl. B01D 65/02
B01D 63/02
B01D 63/08
C02F 1/44

(21)Application number : 07-012947

(71)Applicant : TOTO LTD

(22)Date of filing : 30.01.1995

(72)Inventor : SHIMIZU YASUTOSHI
IZUMI KAZUHIRO
URYU KATSUJI
OKUNO YUICHI

(30)Priority

Priority number : 06 8732 Priority date : 28.01.1994 Priority country : JP

(54) FILTERING METHOD AND FILTER DEVICE

(57)Abstract:

PURPOSE: To efficiently peel the layer of matter to be filtered deposited on the surface of a separation membrane by supplying a predetermined amt. of air to mix the same with a raw soln. to form air bubble streams along the separation membrane.

CONSTITUTION: In a filter device 3, a plurality of plate-shaped membranes 4 are vertically arranged so as to be spaced apart from each other and the suction pipe 6 connected to a pump 5 is connected to the upper end parts of the membranes 4 and a first air diffusion pipes 7 are arranged under the membranes 4 while a second air diffusion pipe 8 is provided on the lateral side of the lower ends of the membranes 4. The first air diffusion pipe 7 forms air bubble streams along the surfaces of the membranes 4 and the second air diffusion pipe 8 applies vibration and an impact to the

